



GEAR OIL SAE 80W-90

Transmission oil

DESCRIPTION	<p>HARTOL GEAR OIL SAE 80W-90 is a mineral-based lubricating oil for mechanical transmissions, formulated with high-quality solvent-refined base oils and special EP additives to obtain the following properties:</p> <ul style="list-style-type: none">• Outstanding oxidation stability.• Effective rust prevention, anti-corrosion and foam inhibiting properties.• Low pour point.• Superior Extreme Pressure (EP) properties.												
APPLICATION	<p>This multi-purpose gear oil is designed for use in hypoid differentials, gearboxes and other transmissions, where an EP-grade transmission oil is recommended .</p>												
SPECIFICATIONS	<ul style="list-style-type: none">• API GL-4												
TYPICAL PROPERTIES	<table><tr><td>• Density at 15 °C, kg/l</td><td>0,890</td></tr><tr><td>• Viscosity 40 °C, mm²/s</td><td>150,50</td></tr><tr><td>• Viscosity 100 °C, mm²/s</td><td>15,20</td></tr><tr><td>• Viscosity Index</td><td>102</td></tr><tr><td>• Flash Point COC, °C</td><td>214</td></tr><tr><td>• Pour Point, °C</td><td>-30</td></tr></table>	• Density at 15 °C, kg/l	0,890	• Viscosity 40 °C, mm ² /s	150,50	• Viscosity 100 °C, mm ² /s	15,20	• Viscosity Index	102	• Flash Point COC, °C	214	• Pour Point, °C	-30
• Density at 15 °C, kg/l	0,890												
• Viscosity 40 °C, mm ² /s	150,50												
• Viscosity 100 °C, mm ² /s	15,20												
• Viscosity Index	102												
• Flash Point COC, °C	214												
• Pour Point, °C	-30												
