



MULTI MTF SAE 75W-80

Transmission fluid

DESCRIPTION	<p>HARTOL Multi MTF SAE 75W-80 – a multi-vehicle manual and automated transmission fluid (MTF), formulated with high-quality base oils in combination with optimized additives, resulting in the following properties:</p> <ul style="list-style-type: none">• Proven compatibility with European and Asian synchronizers• Superior protection for bearings and gears• Excellent cleanliness and deposit control• Reliable performance in low-temperature conditions• Robust corrosion resistance• Extended durability and service life.
-------------	---

APPLICATION	<p>This multi-vehicle manual transmission oil is specially formulated for European and Asian vehicles, including passenger cars and delivery vans, where the specified performance standards are required. This oil is also suitable for applications where similar specifications are recommended in conjunction with slightly different viscosities, such as 70W75, 70W90, 75W, 75W85, 75W90, etc.</p>
-------------	--

SPECIFICATIONS	<ul style="list-style-type: none">• API GL-4• BMW MTF LT-2 / LT-3 / LT-4• Fiat 9.55550-MZ1 / MZ6 / MZ7• Ford WSD-M2C200-C / WSS-M2C200-D2 / ESD-M2C186-A• GM GMW16612 / 1940004 / 19259104• GM 1940182 / 1940764 / 1940768• Honda MTF / MTF-II / MTF-III• MB 235.10• Nissan MT-XZ / MT-XZ TL (JR Type)• PSA B71 2310 / 2315 / 2316 / 2330• Renault DC4 / DW5• Special gear oil, MTF 94• Tranself NFJ/NFP/NFX/TRJ/TRP/TRT/TRX/TRZ• Volvo 97308 / 97309• VW G 009 317 / 052 171 / 052 178 / 052 512• VW G 052 527/052 549/052 726• VW G 50 / 055 512 / 060 726 / 070 726
----------------	--



TYPICAL
PROPERTIES

• Density at 15 °C, kg/l	0,869
• Viscosity 40 °C, mm ² /s	54,40
• Viscosity 100 °C, mm ² /s	9,46
• Viscosity Index	158
• Flash Point COC, °C	222
• Pour Point, °C	-45