



PRIME F SAE 5W-30

Synthetic universal engine oil

DESCRIPTION	<p>HARTOL PRIME F SAE 5W-30 is a high-performance synthetic fuel-efficient engine oil formulated with carefully selected synthetic base oils and a well-balanced blend of advanced additives to deliver the following benefits:</p> <ul style="list-style-type: none">• Reduced fuel consumption• High and stable viscosity index• Excellent shear stability• Reliable cold-start performance• Exceptional resistance to oxidation• Durable lubrication film at high temperatures• Outstanding detergency and dispersion properties• Superior protection against wear, corrosion, and foaming
--------------------	--

APPLICATION	<p>This fuel-efficient synthetic engine oil is recommended for use in gasoline and diesel engines, with or without turbocharging, in passenger cars and light commercial vehicles meeting the specifications listed below. It is specially formulated to meet the latest OEM requirements and is fully backward compatible with Ford M2C 913-A, B, and C specifications.</p>
--------------------	--

SPECIFICATIONS	<ul style="list-style-type: none">• ACEA A5/B5, A1/B1• API SL/CF• Ford WSS-M2C913-D• Jaguar Land Rover TJLR.03.5003• Renault RN0700• VW VWC 53036
-----------------------	--

TYPICALS	<ul style="list-style-type: none">• Density at 15 °C, kg/l• Viscosity -30 °C, mPa.s• Viscosity 40 °C, mm²/s• Viscosity 100 °C, mm²/s• Viscosity Index• Flash Point COC, °C• Pour Point, °C• Total Base Number, mgKOH/g• Sulphate Ash Content, %	<p>0,850 3890 54,50 9,90 170 220 -39 10,1 1,09</p>
-----------------	---	--