



## Versie G SAE 5W-30

### Synthetic universal engine oil

---

<b>DESCRIPTION</b>	<p>HARTOL Versie G SAE 5W-30 is a synthetic universal engine oil, developed according to the most recent technology, based on specially selected synthetic base oils to which special additives are added to obtain the following properties:</p> <ul style="list-style-type: none"><li>• a fast cold start;</li><li>• a safe lubrication film at high temperatures;</li><li>• a very good detergency and dispersion;</li><li>• a very strong protection against wear, corrosion and foaming.</li></ul>
--------------------	---

---

<b>APPLICATION</b>	<p>This synthetic universal "mid SAPS" engine oil is recommended for use in petrol and diesel engines, with or without turbocharging, in passenger cars and delivery vans. Due to its low SAPS content this product can be applied in vehicles with modern three-way catalysts and diesel particle filters.</p>
--------------------	---

---

<b>SPECIFICATIONS</b>	<ul style="list-style-type: none"><li>• ACEA C2, C3</li><li>• API SN</li><li>• BMW Longlife-04</li><li>• GM dexos 2</li><li>• MB 229.51 / 229.52</li><li>• Opel OV 040 1547 - D30</li><li>• VW 505.01</li></ul>
-----------------------	---

---

<b>TYPICAL PROPERTIES</b>	<ul style="list-style-type: none"><li>• Density at 15 °C, kg/l</li><li>• Viscosity -30 °C, mPa.s</li><li>• Viscosity 40 °C, mm<sup>2</sup>/s</li><li>• Viscosity 100 °C, mm<sup>2</sup>/s</li><li>• Viscosity Index</li><li>• Flash Point COC, °C</li><li>• Pour Point, °C</li><li>• Total Base Number, mgKOH/g</li><li>• Sulphate Ash, %</li></ul>	<p>0,855 6000 73,00 12,10 163 230 -36 7,8 0,77</p>
---------------------------	---	--

---