



ODYSSEUS SAE 10W-40

Multigrade engine oil

DESCRIPTION	HARTOL ODYSSEUS SAE 10W-40 is a multigrade engine oil formulated based on special base oils with a naturally high viscosity index and additives to obtain the following properties: <ul style="list-style-type: none">• High and stable viscosity index.• Quick cold start capability.• Robust oxidation resistance.• Secure lubricating film at high temperatures.• Effective detergency and dispersing properties.• Reliable protection against wear, corrosion, and foaming.
--------------------	--

APPLICATION	Universal engine oil recommended for use in gasoline and diesel engines, with or without a turbocharger, of passenger cars and vans.
--------------------	--

SPECIFICATIONS	<ul style="list-style-type: none">• ACEA A3/B3• API SL/CF• MB 229.1• VW 501.01/505.00
-----------------------	--

TYPICAL PROPERTIES	<ul style="list-style-type: none">• Density at 15 °C, kg/l• Viscosity -20 °C, mPa.s• Viscosity 40 °C, mm²/s• Viscosity 100 °C, mm²/s• Viscosity Index• Flash Point COC, °C• Pour Point, °C• Total Base Number, mgKOH/g• Sulphate Ash, %	<ul style="list-style-type: none">0,872470092,0013,80153232-398,31,08
---------------------------	---	---